

**MATERIAL SAFETY DATA SHEET**  
**Essentially Similar to U.S. Department of Labor Form OSHA**  
**Revised: 01/20/12**  
**HMIS Health-1 Flammability-3 Reactivity 0**  
**SECTION I-Product Information**

**Manufacturer: A.V.W. Inc.**  
**24 Hour Emergency Phone Number: 800-424-9300**  
**Product Name: Blow Off Rubber Rejuvenator**

**SECTION II-Hazardous Ingredients**

Xylene	CAS#	95-47-6	TWA	100
Methanol	CAS#	67-56-1	TWA	200
Mineral Spirit	CAS#	8052-41-3	TWA	200
Acetone	CAS#	67-64-1	TWA	1000
Isopropanol	CAS#	6763-0	TWA	400
Propane	CAS#	74-98-6	TWA	1000
Butane	CAS#	106-97-8	TWA	800

**SECTION III-Physical Data**

Boiling Point: 188 F  
Specific Gravity (H20=1)=.86  
Solubility in Water: .0%  
Appearance: Colorless liquid with penetrating ether like odor.

**SECTION IV-Fire and Explosion Hazard Data**

Flash Point: 98 F Extremely Flammable Level 3 Aerosol  
Extinguishing Media: Water, CO2, Foam, Dry Chemical  
Special Fire Fighting Procedures: Do not expose containers to temperatures above 120 F.  
Unusual Fire and Explosion: Forms flammable vapor air mixtures. Lower temperatures increase the difficulty of getting it to ignite.

**SECTION V-Health Hazard and First Aid**

Time Weighted Average (TWA): 100 ppm based in the raw material.  
Carcinogen: No  
Acute Chronic Health Effects: Excessive exposure may cause irritation to upper respiratory tract. Excessive exposure may cause carboxyhemoglobinemia, thereby impairing the bloods ability to transport oxygen.  
Primary Routes of Entry: X Inhalation X Skin X Ingestion  
Effects of Overexposure: Eyes- May cause pain, moderate eye irritation and slight corneal injury. Vapors may irritate eyes.  
Skin- May cause irritation. Repeated contact may cause drying or flaking of the skin.  
Inhalation- In confined or poorly ventilated areas, vapors can readily accumulate and cause unconsciousness and death.  
Ingestion- May be harmful.  
First Aid:  
Eyes- Flush with water for 15 minutes. If irritation persists get medical attention.  
Skin- Wash with soap and water.  
Inhalation- Move to fresh air. Get medical attention.  
Ingestion- Do not induce vomiting. Get medical attention immediately.

**SECTION VI-Reactivity Data**

Stability: Stable X  
Conditions to Avoid: Hydrolysis producing small amounts of hydrochloric acid possible with gross water contamination. Avoid open flames, welding arcs, or other high temperature sources, which induce thermal decomposition.  
Incompatibility: Strong oxidizers; caustics, chemically active metals such as aluminum, magnesium and sodium.

**SECTION VII-Spill or Leak Procedures**

Steps to take in case material is spilled or released: Use absorbent material and trash receptacle. Waste disposal method Federal and Local regulations.

**SECTION VIII-Special Protection Information**

Respiratory Protection: Adequate ventilation  
Gloves (type): Chemical resistant  
Eye Protection: Glasses (if required)  
Other Protective Equipment: None

**SECTION IX-Special Precautions**

Precautions to be taken in handling and storing: Read and follow all label directions. Do not store containers at temperatures above 120 F.

**SECTION X- WHMIS CLASSIFICATION**

WHMIS Class B -Flammable and Combustible Material  
Division 5- Flammable Aerosol